

# Galvanized Steel Undercarriage

Series 6913

**REMCO**

## Durable Frame

The minimal steel construction makes this undercarriage a nimble yet durable transporting solution



## Rust-Resistant Material

Galvanized steel resists corrosion and helps the undercarriage last longer while looking new

## Pivoting Wheels

Allow for nimble maneuvering of transport tubs

This galvanized steel low undercarriage features castor wheels that are impervious to meat fat and bearings equipped with grease fittings. The zinc coating on the steel keeps the undercarriage free from rust, even in very moist environments. A low undercarriage is a great solution when mobility is required.



**Galvanized Steel Undercarriage**

6913

*Available in steel only*

This tub accessory is commonly used for meat, seafood, poultry, commercial fishing, confectionery, bakery, and grain applications. Replacement casters and wheels are available.

**Specifications:**

- Length: 42.5"
- Width: 21.6"
- Height: 9.4"
- FDA-Compliant Raw Material: No
- Material: Galvanized Steel
- Unit Weight: 57.5 lbs.

**Colors**

When ordering, add the color digit to the base part number to denote color.



Fully updated product specifications are available at [Remcoproducts.com](http://Remcoproducts.com).

**The Color-Coding System**

Remco and Vikan® brands offer an integrated color-coding system to help mitigate the risk of cross-contamination in food processing facilities. With an array of color-coded tools and storage brackets, and years of experience building effective color-coding systems, the experts at Remco Products Corporation can help you effectively apply color-coding to divide and identify different zones or processing tasks. As a result, workers can more easily comply with material handling and hygienic cleaning procedures to maintain stringent food safety standards.



Please see the full-line catalog for a complete list of Remco™ and Vikan® products.



**Remco Products Corporation**

4735 West 106th Street  
Zionsville, Indiana 46077

PHONE: 317.876.9856 | FAX: 800.585.8619

[www.remcoproducts.com](http://www.remcoproducts.com)

